WEBSITE C-MAIL

EARTHING EQUIPMENTS

EARTH RODS

Cọc tiếp địa Axis phi 14 hoặc 16 mm (5/8") dài 2.4 mét

Driving Stud

AXIS offers to the customer a complete range of earthing equipments which are best suitable and most economically available.

INDEX

COPPER BONDED EARTH RODS - SECTIONAL

AXIS earth rods are made from high tensile low carbon steel. Each rod is made by molecularly bonding 99.9 % pure electrolytic copper. To prevent oxidation of copper bonding, each rod is treated with Benzol - triozole derivatives. Threads on the rods are formed by roll threading process giving extra strength to the threads and eliminating risk of chipping of threads while driving the rod in the ground.

ROD DETAILS - for Vietnam market only

Rod DIA.mm	Total Length	Thread Dia	E - Code
14.0	2400	5/8"	(A)CBR1624TRE
14.0	3000	5/8"	(A)CBR1430TRE
16.0	2400	5/8"	(A)CBR1824TRE



Coupler

Coupler



THREADED COUPLERS

Made up of Copper Alloy for higher strength and countered bored to protect the rod threads from damage.

Earth Rod

Thread Dia	E-Code.	Thread Dia	E-Code
9/16"	BC0916	9/16"	DB0916
5/8"	BC0058	5/8"	DB0058
3/4"	BC0034	3/4"	DB0034

- * http://BaoMinhTech.com: nhà phân phối cọc tiếp địa Axis Ấn Độ:
- Cọc tiếp địa Axis phi 14 mm dài 2.4 mét.
- Cọc tiếp địa Axis phi 16 mm dài 2.4 mét.
- * Liên hệ: 0917 650 109 Email: baominhtech@gmail.com Web: http://chongset.org

DRIVING BOLT

for power hammering.

Made up of Re-usable high tensile steel

Can be used many times over and suitable

